

# Tecna balancer

# Tecna balancer



## Tecna balancer / Tecna balancer



### Med aluminiumshus og rustfri stålwire / With aluminium housing and stainless steel wire

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9310	0,2	0,5	1.600	0,55
78.9311	0,4	1	1.600	0,6
78.9312	1	2	1.600	0,6
78.3913	2	3	1.600	0,7
78.9320	1	2,5	2.000	1,6
78.9321	2	4	2.000	1,9
78.9322	4	6	2.000	2
78.9323	6	8	2.000	2,3
78.9354	4	7	2.000	5
78.9355	7	10	2.000	5,5
78.9356	10	14	2.000	5,7
78.9357	14	18	2.000	6
78.9358	18	22	2.000	6,5
78.9359	22	25	2.000	6,7
78.9361	10	15	2.000	10,3
78.9362	15	20	2.000	10,6
78.9363	20	25	2.000	11,2
78.9364	25	30	2.000	11,5
78.9365	30	35	2.000	11,8
78.9366	35	45	2.000	12,4
78.9367	45	55	2.000	12,5
78.9368	55	65	2.000	13,6
78.9369	65	75	2.000	14,5
78.9370	75	90	2.000	17,3
78.9371	90	105	2.000	18,0
78.9401	15	20	2.500	19,0
78.9402	20	30	2.500	19,8
78.9403	30	40	2.500	20,8

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9404	40	50	2.500	23,9
78.9405	50	60	2.500	25,4
78.9411	60	70	2.500	26,8
78.9412	70	80	2.500	27,8
78.9413	80	90	2.500	28,8
78.9414	90	100	2.500	30,0
78.9422	100	120	2.500	38,7
78.9423	120	140	2.500	41,9
78.9424	130	150	2.500	44,5
78.9425	140	160	2.500	48,0
78.9426	160	180	2.500	49,0
78.9431	15	20	3.000	19,7
78.9432	20	25	3.000	19,7
78.9433	25	35	3.000	21,2
78.9434	35	45	3.000	23,8
78.9435	40	50	3.000	23,9
78.9436	50	60	3.000	25,3
78.9441	60	70	3.000	27
78.9442	70	80	3.000	28
78.9443	80	90	3.000	29
78.9444	80	100	3.000	29
78.9451	100	115	3.000	39,7
78.9452	115	130	3.000	39,9
78.9453	130	140	3.000	42,8
78.9454	140	150	3.000	45,6
78.9455	150	160	3.000	49
78.9456	160	180	3.000	50

## Tecna balancer / Tecna balancer

### Med nylonhus og rustfri stålwire /

With aluminium housing and stainless steel wire with STOP

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9300	0,2	0,5	1.600	0,5
78.9301	0,4	1	1.600	0,5
78.9302	1	2	1.600	0,6
78.9303	2	3	1.600	0,7

### Med aluminiumshus og rustfri stålwire med STOP /

With aluminium housing and stainless steel wire with STOP

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9346	2	4	2.500	3,2
78.9347	4	6	2.500	3,3
78.9348	6	8	2.500	3,4
78.9349	8	10	2.500	3,5
78.9350	10	14	2.500	3,7

### Med aluminiumshus og 4.500 mm rustfri stålwire med STOP /

With aluminium housing and 4.500 mm stainless steel wire with STOP

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9346D	2	4	4.500	3,2
78.9347D	4	6	4.500	3,3
78.9348D	6	8	4.500	3,4
78.9349D	8	10	4.500	3,5
78.9350D	10	14	4.500	3,6

### Med aluminiumshus og dyneema wire / With aluminium housing and dyneema wire

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9336	2	4	2.500	2,9
78.9337	4	6	2.500	3,2
78.9338	6	8	2.500	3,5
78.9339	8	10	2.500	3,7
78.9340	10	14	2.500	4,0

### Til luft med 1/4" polyurethan slange / For air with 1/4" polyurethane hose

Varenr. Art.	Kapacitet		Wire mm	Egenvægt kg
	Min.	Maks.		
78.9200	0,4	0,8	1.350	1,25
78.9201	0,75	1,5	1.350	1,30
78.9202	1,2	2,5	1.350	1,35
78.9203	3	5	900	1,35